

## THE ADVANTAGES OF THE SEB

Metric threads: M8 → M48

UNC threads: UNC 3/8"-16 → UNC 1" 1/2-6

Safety factor: 5 and 4

Machinery Directive 2006/42/CE

Norm EN 1677-1

Individual traceability number

Operating temperature: -20°C → + 200°C

Swiveling under load (360° rotation)

Available in female and stainless steel version



#### Your technical and quality advantages

Usable for any kind of lifting operation		absolute safety for any kind of lifting situation, no r
(straight lifts, with angle, turning, rotating)	7	wrong use
Automatic orientation in the direction of pulling	_	no need to manually orientate the lifting ring

Verification of each thread with calibrated gauge

Clear markings (CE, WLL, tightening torque)

Individual packaging and documents, delivery in sturdy packaging

Anti-tribocorrosion grease for life

Solid rotation bushing

**Centering system** 

Anti-corrosion coating (zinc coating) on bolt and base

- risk of
- no friction between shackle and object to be lifted, easy rotation under load
- no costs related to non-conformity, lifting rings can directly be put in use
- reduction risk of incorrect use
- quality and easy handling
- easy rotation under load, built-in corrosion protection
- limiting risk of corrosion in critical environments, durability of products

**ALITRACER** 

- possibility to increase WLL at 90°
- suivi optimal (contrôle, gestion de stock ...)

Short delivery times for standard products and specials guaranteed	no production breakdowns, operational gains, stock reduction
No minimum order quantity	→ stock reduction, quick fixes
Multilingual sales team	ease of communication, professional support
Fast on custom-made solution (case study and testing)	→ solution for special lifting applications
Experience of over 40 years	→ pledge of seriousness and professionalism
Free annual inspection at our factory	maintaining high safet level as annual check is conducted by the manufacturer
ISO and UNC as standard threads, special thread (optional)	one partner for your needs of swivel lifting rings
High quality material and marketing supports	→ videos, samples, technical drawings





# THE ADVANTAGES OF THE DSR

Metric threads: M5 → M42

UNC threads: UNC 1/4"-20 → UNC 1" 1/4-7

Safety factor: 5 and 4

Machinery Directive 2006/42/CE

Norm EN 1677-1

Individual traceability number

Operating temperature: -20°C → + 200°C

Swiveling under load (360° rotation and 180° swivel)

Available in female, stainless steel and weld-on version



### Your technical and quality advantages

Usable for any kind of lifting operation (straight lifts, with angle, turning, rotating)	absolute safety for any kind of lifting situation, no risk of wrong use
Two possibilities of tightening and protection of bolt head	flexibility during implementation, fast assembly, thread is protected from the hook
Verification of each thread with calibrated gauge	no costs related to non-conformity, lifting rings can directly be put in use
Clear markings (CE, WLL, tightening torque)	→ reduction risk of incorrect use
Individual packaging and documents, delivery in sturdy packaging	→ quality and easy handling
Anti-tribocorrosion grease for life	easy rotation under load, built-in corrosion protection
Anti-corrosion coating (zinc coating) on bolt, bushing and base	ilmiting risk of corrosion in critical environments, durability of products
Centering system	→ possibility to increase WLL at 90°
Blocking springs	→ help to connect the hook more easily
Adhesive protective washer SCP	→ protection for highly sensitive surface
ALITRACER	effective follow-up (inspections, stock management)

Short delivery times for standard products and specials guaranteed	no production breakdowns, operational gains, stock reduction
No minimum order quantity	→ stock reduction, quick fixes
Multilingual sales team	→ ease of communication, professional support
Fast on custom-made solution (case study and testing)	→ solution for special lifting applications
Experience of over 40 years	pledge of seriousness and professionalism
Free annual inspection at our factory	maintaining high safet level as annual check is conducted by the manufacturer
ISO and UNC as standard threads, special thread (optional)	→ one partner for your needs of swivel lifting rings
High quality material and marketing supports	→ videos, samples, technical drawings





# THE ADVANTAGES OF THE DSS

Metric threads: M24 → M100

UNC threads: UNC 1"-8 → UNC 2" 1/2-4

Safety factor: 5 and 4

Machinery Directive 2006/42/CE

Norm EN 1677-1

Individual traceability number

Operating temperature: -20°C → + 200°C

Swiveling under load (360° rotation and 180° swivel)

Available in female, stainless steel and weld-on version



### Your technical and quality advantages

Usable for any kind of lifting operation (straight lifts, with angle, turning, rotating)	absolute safety for any kind of lifting situation, no risk of wrong use
Optimized WLL/dimensions and weight ratio	wide shackle opening for installation of the hook, easy to use, high performance
Verification of each thread with calibrated gauge	no costs related to non-conformity, lifting rings can directly be put in use
Clear markings (CE, WLL, tightening torque)	→ reduction risk of incorrect use
Individual packaging and documents, delivery in sturdy packaging	→ quality and easy handling
Anti-tribocorrosion grease for life	easy rotation under load, built-in corrosion protection
Anti-corrosion coating (zinc coating) on bolt and base	ilmiting risk of corrosion in critical environments, durability of products
0.6	A

YOUR

Centering system

**Blocking springs** 

ALITRACER

- → possibility to increase WLL at 90°
- help to connect the hook more easily
- effective follow-up (inspections, stock management ...)

Short delivery times for standard products and spe- cials guaranteed	no production breakdowns, operational gains, stock reduction
No minimum order quantity	→ stock reduction, quick fixes
Multilingual sales team	→ ease of communication, professional support
Fast on custom-made solution (case study and testing)	→ solution for special lifting applications
Experience of over 40 years	pledge of seriousness and professionalism
Free annual inspection at our factory	maintaining high safet level as annual check is conducted by the manufacturer
ISO and UNC as standard threads, special thread (optional)	→ one partner for your needs of swivel lifting rings
High quality material and marketing supports	→ videos, samples, technical drawings





# THE ADVANTAGES OF THE MEGA DSS

Metric threads: M64 → M100

UNC threads: UNC 2" 3/4-4 → UNC 4"-4

Safety factor: 5 and 4

Machinery Directive 2006/42/CE

Norm EN 1677-1

Individual traceability number

Operating temperature: -20°C → + 200°C

Swiveling under load (360° rotation and 180° swivel)



### Your technical and quality advantages

Usable for any kind of lifting operation (straight lifts, with angle, turning, rotating)	absolute safety for any kind of lifting situation, no risk of wrong use
Optimized WLL/dimensions and weight ratio	wide shackle opening for installation of the hook, easy to use, high performance
Verification of each thread with calibrated gauge	no costs related to non-conformity, lifting rings can directly be put in use
Clear markings (CE, WLL, tightening torque)	→ reduction risk of incorrect use
Individual packaging and documents, delivery in sturdy packaging	→ quality and easy handling
Anti-tribocorrosion grease for life	easy rotation under load, built-in corrosion protection
Anti-corrosion coating (zinc coating) on bolt and base	imiting risk of corrosion in critical environments, durability of products

ALITRACER

effective follow-up (inspections, stock management ...)

Short delivery times for standard products and specials guaranteed	no production breakdowns, operational gains, stock reduction
No minimum order quantity	→ stock reduction, quick fixes
Multilingual sales team	→ ease of communication, professional support
Fast on custom-made solution (case study and testing)	→ solution for special lifting applications
Experience of over 40 years	pledge of seriousness and professionalism
Free annual inspection at our factory	maintaining high safet level as annual check is conducted by the manufacturer
ISO and UNC as standard threads, special thread (optional)	one partner for your needs of swivel lifting rings
High quality material and marketing supports	→ videos, samples, technical drawings

